

View Online at <https://aerobasegroup.com/nsn/5910-01-065-7564>

**Thread Class:**

2a

**Body Style:**

Piston

**Overall Length:**

0.734 inches

**Terminal Length:**

0.097 inches

**Bushing Diameter:**

0.234 inches

**Bushing Length:**

0.234 inches

**Body Length:**

0.500 inches

**Overall Diameter:**

Between 0.275 inches and 0.295 inches

**Temperature Coefficient Of Capacitance In Ppm Per Deg Celsius:**

0.0 single section

**Tolerance Of Temperature Coefficient In Ppm Per Deg Celsius:**

-30.0/+30.0 single section

**Quality Factor At 25 Deg Celsius:**

1500.0

**Fragility Factor:**

Moderately rugged

**Terminal Width:**

0.097 inches

**Terminal Thickness:**

0.020 inches

**Mounting Facility Screw Thread Series Designator:**

Uns

**Inclosure Type:**

Encased

**Tuning Characteristic:**

Straight line capacity single section

**Adjustment Device Torque:**

Between 1.000 inch-ounces and 5.000 inch-ounces

**Bushing Shape:**

Round

**Insulation Dc Resistance At 25 Deg Celsius:**

100000.0 megohms

**Mounting Facility Type And Quantity:**

1 locking bushing

**Thready Qty Per Inch (tpi):**

64

**Nonderated Operating Temp:**

Between -65.0 degrees celsius and 125.0 degrees celsius

**Thread Size:**

0.234 inches

**Capacitance Range In Picofarads:**

+1.0/+20.0 single section

**Nonderated Voltage Rating And Type:**

250.0 dc continuous single section

**Adjustment Device Drive Type And Quantity:**

1 slotted screw

**Capacitance Drift In Picofarads:**

0.01 single section

**Material:**

Metal base

**Terminal Type And Quantity:**

1 tab, solder lug

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A096a0