NSN 5910-01-066-3015

Ceramic Dielectric Fixed Capacitor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5910-01-066-3015

Body Style: W/o mtg facilities, terminals on opposite surfaces Reliability Indicator: Not established **Terminal Length:** 1.250 inches **Body Length:** 0.300 inches **Body Width:** 0.150 inches **Body Height:** 0.300 inches **Terminal Diameter:** 0.025 inches **Schematic Diagram Designator:** No common or grounded electrode (s) **Capacitance Value Per Section:** 100.000 picofarads single section **Nonderated Operating Temp:** Between -55.0 degrees celsius and 125.0 degrees celsius Tempurature Coefficient Of Capacitance Per Section In Ppm Per Deg Celsius: 0.0 single section Nonderated Continuous Voltage Rating And Type Per Section: 500.0 dc single section **Tolerance Of Tempurature Coefficient Per Section In Ppm Per Deg Celsius:** -20.0/+20.0 single section **Tolerance Range Per Section:** -1.00/+1.00 percent single section **Case Material: Plastic Insulation Resistance At Reference Temp:** 1000.0 megohm-microfarads **Dissipation Factor At Reference Tempurature In Percent:** 0.0010 **Power Factor At Reference Tempurature In Percent:** 0.1000 **Test Data Document:** 26055-821-032-000 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing,

etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing)

Terminal Type And Quantity:

2 uninsulated wire lead

Shelf Life:

N/a

NSN 5910-01-066-3015

Ceramic Dielectric Fixed Capacitor - Page 2 of 2



ш	ın	10	<i>(</i>)+	Measure:	

--

Demilitarization:

No

Fiig:

A010b0