NSN 5910-01-066-3024

Ceramic Dielectric Fixed Capacitor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5910-01-066-3024

view offilite at https://defobasegroup.com/hsh/os/10-01-000-3024
Body Style:
W/o mtg facilities, terminals on opposite surfaces
Reliability Indicator:
Not established
Terminal Length:
1.250 inches
Body Length:
0.400 inches
Body Width:
0.150 inches
Body Height:
0.400 inches
Terminal Diameter:
0.025 inches
Schematic Diagram Designator:
No common or grounded electrode (s)
Capacitance Value Per Section:
3000.000 picofarads single section
Nonderated Operating Temp:
Between -55.0 degrees celsius and 125.0 degrees celsius
Tempurature Coefficient Of Capacitance Per Section In Ppm Per Deg Celsius:
0.0 single section
Nonderated Continuous Voltage Rating And Type Per Section:
500.0 dc single section
Tolerance Of Tempurature Coefficient Per Section In Ppm Per Deg Celsius:
-20.0/+20.0 single section
Tolerance Range Per Section:
-0.50/+0.50 percent single section
Case Material:
Plastic
Insulation Resistance At Reference Temp:
1000.0 megohm-microfarads
Dissipation Factor At Reference Tempurature In Percent:
0.0010
Power Factor At Reference Tempurature In Percent:
0.1000
Test Data Document:
26055-821-032-000 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing
etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing)

Terminal Type And Quantity:

2 uninsulated wire lead

Shelf Life:

N/a

NSN 5910-01-066-3024

Ceramic Dielectric Fixed Capacitor - Page 2 of 2



		• •			
ш	ın	10	<i>(</i>)+	Measure:	

--

Demilitarization:

No

Fiig:

A010b0