

View Online at <https://aerobasegroup.com/nsn/5910-01-066-4956>

**Thread Class:**

2a

**Body Style:**

Piston

**Overall Length:**

0.578 inches

**Terminal Length:**

0.500 inches

**Bushing Diameter:**

0.234 inches

**Bushing Length:**

0.102 inches

**Body Length:**

Between 0.272 inches and 0.322 inches

**Overall Diameter:**

0.281 inches

**Temperature Coefficient Of Capacitance In Ppm Per Deg Celsius:**

0.0 single section

**Tolerance Of Temperature Coefficient In Ppm Per Deg Celsius:**

-50.0/+50.0 single section

**Center To Center Distance Between Terminals Parallel To Length:**

0.281 inches

**Center To Center Distance Between Terminals Parallel To Diameter:**

0.219 inches

**Quality Factor At 25 Deg Celsius:**

3000.0

**Mounting Facility Screw Thread Series Designator:**

Uns

**Inclosure Type:**

Encased

**Tuning Characteristic:**

Straight line capacity single section

**Adjustment Device Torque:**

Between 0.500 inch-ounces and 0.600 inch-ounces

**Bushing Shape:**

Round

**Insulation Dc Resistance At 25 Deg Celsius:**

1000000.0 megohms

**Insulation Dc Resistance At Max Operating Temp:**

100000.0 megohms

**Mounting Facility Type And Quantity:**

1 threaded bushing

**Thready Qty Per Inch (tpi):**

64

**Nonderated Operating Temp:**

Between -55.0 degrees celsius and 125.0 degrees celsius

**Thread Size:**

0.234 inches

**Capacitance Range In Picofarads:**

+1.0/+14.0 single section

**Nonderated Voltage Rating And Type:**

250.0 dc continuous single section

**Adjustment Device Drive Type And Quantity:**

1 slotted screw

**Capacitance Drift In Picofarads:**

0.02 single section

**Test Data Document:**

81349-mil-c-14409 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

**Terminal Type And Quantity:**

2 printed circuit

**Specification Data:**

81349-mil-c-14409/13 government specification

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A096a0