Air Dielectric Variable Capacitor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5910-01-066-4956

View Online at https://aerobasegroup.com/nsn/5910-01-066-4956
Thread Class:
2a
Body Style:
Piston
Overall Length:
0.578 inches
Terminal Length:
0.500 inches
Bushing Diameter:
0.234 inches
Bushing Length:
0.102 inches
Body Length:
Between 0.272 inches and 0.322 inches
Overall Diameter:
0.281 inches
Tempurature Coefficient Of Capacitance In Ppm Per Deg Celsius:
0.0 single section
Tolerance Of Tempurature Coefficient In Ppm Per Deg Celsius:
-50.0/+50.0 single section
Center To Center Distance Between Terminals Parallel To Length:
0.281 inches
Center To Center Distance Between Terminals Parallel To Diameter:
0.219 inches
Quality Factor At 25 Deg Celsius:
3000.0
Mounting Facility Screw Thread Series Designator:
Uns
Inclosure Type:
Encased
Tuning Characteristic:
Straight line capacity single section
Adjustment Device Torque:
Between 0.500 inch-ounces and 0.600 inch-ounces
Bushing Shape:
Round
Insulation Dc Resistance At 25 Deg Celsius:
1000000.0 megohms
Insulation Dc Resistance At Max Operating Temp:
100000.0 megohms
Mounting Facility Type And Quantity:
1 threaded bushing

Air Dielectric Variable Capacitor - Page 2 of 2



Thready Qty Per Inch (tpi):

64

Nonderated Operating Temp:

Between -55.0 degrees celsius and 125.0 degrees celsius

Thread Size:

0.234 inches

Capacitance Range In Picofarads:

+1.0/+14.0 single section

Nonderated Voltage Rating And Type:

250.0 dc continuous single section

Adjustment Device Drive Type And Quantity:

1 slotted screw

Capacitance Drift In Picofarads:

0.02 single section

Test Data Document:

81349-mil-c-14409 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

Terminal Type And Quantity:

2 printed circuit

Specification Data:

81349-mil-c-14409/13 government specification

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A096a0