

View Online at <https://aerobasegroup.com/nsn/5910-01-066-6073>

Body Style:

Chip type

Reliability Indicator:

Established

Reliability Failure Rate Level In Percent:

1.000

Terminal Length:

0.025 inches

Body Length:

0.100 inches

Body Width:

0.060 inches

Body Height:

0.055 inches

Center To Center Distance Between Terminals Parallel To Length:

0.050 inches

Schematic Diagram Designator:

No common or grounded electrode (s)

End Application:

Kg-46/tsec

Insulation Resistance At Maximum Operating Temp:

10000.0 megohms

Capacitance Value Per Section:

1000.000 picofarads single section

Nonderated Operating Temp:

Between 55.0 degrees celsius and 125.0 degrees celsius

Nonderated Continuous Voltage Rating And Type Per Section:

50.0 dc single section

Tolerance Range Per Section:

-10.00/+10.00 percent single section

Case Material:

Ceramic

Insulation Resistance At Reference Temp:

100000.0 megohms

Dissipation Factor At Reference Temperature In Percent:

2.5000

Terminal Surface Treatment:

Solder

Special Features:

Selected item; type designation: cdr01bx102bksm

Test Data Document:

81349-mil-c-55681b/1a specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). And 98230-0n225132 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any

Terminal Type And Quantity:

2 bonding pad

Specification Data:

81349-mil-c-55681d/1a government specification

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A010b0