Plastic Dielectric Fixed Capacitor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5910-01-066-6272

## **Body Style:**

W/o mtg facilities terminal (s) on one surface

**Reliability Indicator:** 

Not established

# **Terminal Length:**

1.410 inches

Body Length:

0.800 inches

#### **Body Width:**

0.580 inches

**Body Height:** 

#### 0.250 inches

### Center To Center Distance Between Terminals Parallel To Length:

0.375 inches

#### **Terminal Diameter:**

0.032 inches

### Schematic Diagram Designator:

No common or grounded electrode (s)

### Internal Electrical Connection Type:

Extended foil

## Insulation Resistance At Maximum Operating Temp:

1500.0 megohm-microfarads

## Capacitance Value Per Section:

6800.000 picofarads single section

### Nonderated Operating Temp:

Between -40.0 degrees celsius and 85.0 degrees celsius

### Nonderated Continuous Voltage Rating And Type Per Section:

400.0 dc single section

### **Tolerance Range Per Section:**

-10.00/+10.00 percent single section

#### **Case Material:**

Plastic

## Insulation Resistance At Reference Temp:

25000.0 megohm-microfarads

# Dissipation Factor At Reference Tempurature In Percent:

1.0000

## **Terminal Surface Treatment:**

Solder

## **Dielectric Material:**

Plastic polyester

#### **Special Features:**

Crimped leads



# Terminal Type And Quantity:

2 uninsulated wire lead

Shelf Life:

N/a

Unit Of Measure:

---

Demilitarization:

No

Fiig:

A010b0