# NSN 5910-01-067-7324

Ceramic Dielectric Fixed Capacitor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5910-01-067-7324

Body Style:
W/o mtg facilities terminal (s) on one surface
Reliability Indicator:
Established
Reliability Failure Rate Level In Percent:
0.0100
Terminal Length:
1.250 inches
Body Length:
0.480 inches
Body Width:
0.480 inches
Body Height:
0.200 inches
Center To Center Distance Between Terminals Parallel To Length:
0.400 inches
Terminal Diameter:
Between 0.024 inches and 0.029 inches
Schematic Diagram Designator:
No common or grounded electrode (s)
Insulation Resistance At Maximum Operating Temp:
10000.0 megohms
Capacitance Value Per Section:
0.100 microfarads single section
Nonderated Operating Temp:
Between -55.0 degrees celsius and 125.0 degrees celsius
Tempurature Coefficient Of Capacitance Per Section In Ppm Per Deg Celsius:
0.0 single section
Nonderated Continuous Voltage Rating And Type Per Section:
50.0 dc single section
Tolerance Of Tempurature Coefficient Per Section In Ppm Per Deg Celsius:
-30.0/+30.0 single section
Tolerance Range Per Section:
-2.00/+2.00 percent single section
Case Material:
Plastic
Insulation Resistance At Reference Temp:
100000.0 megohms
Dissipation Factor At Reference Tempurature In Percent:
0.1500
Terminal Surface Treatment:

Solder

## NSN 5910-01-067-7324

Ceramic Dielectric Fixed Capacitor - Page 2 of 2



#### **Special Features:**

Nuclear hardness critical item, no drawing to determine if isc code 1 item should also be nuclear hardness. Can't change criticality code to reflect nuclear hardness

#### **Test Data Document:**

81349-mil-c-20 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

### **Terminal Type And Quantity:**

2 uninsulated wire lead

#### **Specification Data:**

81349-mil-c-20/37 government specification

Shelf Life:

N/a

**Unit Of Measure:** 

**Demilitarization:** 

No

Fiig:

A010b0