

View Online at https://aerobasegroup.com/nsn/5910-01-067-7406

| New Online at https://aerobasegroup.com/hsi//3910-01-007-7400 |
|---|
| Body Style: |
| Rotary |
| Overall Height: |
| 0.163 inches |
| Overall Diameter: |
| Between 0.203 inches and 0.233 inches |
| Center To Center Distance Between Terminals Parallel To Diameter: |
| Between 0.180 inches and 0.210 inches |
| Quality Factor At 25 Deg Celsius: |
| 500.0 |
| Inclosure Type: |
| Encased |
| Adjustment Device Torque: |
| Between 0.500 inch-ounces and 3.000 inch-ounces |
| Insulation Dc Resistance At 25 Deg Celsius: |
| 10.0 gigohms |
| Mounting Facility Type And Quantity: |
| 2 terminal |
| Nonderated Operating Temp: |
| Between -55.0 degrees celsius and 85.0 degrees celsius |
| Capacitance Range In Picofarads: |
| +5.0/+25.0 single section |
| Nonderated Voltage Rating And Type: |
| 100.0 dc continuous single section |
| Capacitance Change In Percent At Operating Tempurature From 25 Deg Celsius: |
| -4.50/+2.00 single section and -2.50/+2.00 single section |
| Adjustment Device Drive Type And Quantity: |
| 1 slotted screw |
| Precious Material And Location: |
| Terminal surface silver |
| Precious Material: |
| Silver |
| Terminal Type And Quantity: |
| 2 tab, solder lug |
| Shelf Life: |
| N/a |
| Unit Of Measure: |
| |
| Demilitarization: |
| No |
| Fiig: |
| A096a0 |