Electrolytic Fixed Capacitor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5910-01-068-2213

### **Body Style:**

W/o mtg facilities, axial terminals

**Reliability Indicator:** 

Not established

Terminal Length:

1.500 inches

### **Body Diameter:**

0.406 inches

**Body Length:** 

2.874 inches

**Terminal Diameter:** 

0.025 inches

Schematic Diagram Designator:

No common or grounded electrode (s)

#### Anode Type:

Plain foil

## Impedance At Minimum Operating Tempurature In Ohms:

562.0

## **Electrical Polarization:**

Nonpolarized

## Capacitance Value Per Section:

3.900 microfarads single section

## Nonderated Operating Temp:

Between -55.0 degrees celsius and 85.0 degrees celsius

## Dc Leakage At Maximum Operating Temp:

325.0 microamperes

## Nonderated Continuous Voltage Rating And Type Per Section:

375.0 dc single section

#### **Tolerance Range Per Section:**

-15.00/+15.00 percent single section

#### Case Material:

Metal

## **Capacitive Electrode Material:**

Tantalum

# Dissipation Factor At Reference Tempurature In Percent:

10.0000

## Dc Leakage At Reference Temp:

50.000 microamperes

## **Terminal Surface Treatment:**

Solder

## **Case Insulation Material:**

Plastic

Electrolytic Fixed Capacitor - Page 2 of 2



# Terminal Type And Quantity:

2 uninsulated wire lead

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A010b0