

View Online at <https://aerobasegroup.com/nsn/5910-01-068-2776>

Body Style:

W/thd mtg hole/stud, terminal (s) on one end

Reliability Indicator:

Not established

Width Across Flats:

0.187 inches

Body Diameter:

0.187 inches

Body Length:

0.359 inches

Schematic Diagram Designator:

Feedthrough

Mounting Facility Screw Thread Series Designator:

Unc

Mounting Facility Type And Quantity:

1 threaded bushing

Capacitance Value Per Section:

100.000 picofarads single section

Voltage Temperature Limits Per Section In Percent Capacitance Change:

-33.0/+22.0 with rated voltage applied single section

Nonderated Operating Temp:

Between -55.0 degrees celsius and 125.0 degrees celsius

Thread Size:

0.250 inches

Nonderated Continuous Voltage Rating And Type Per Section:

100.0 dc single section

Tolerance Range Per Section:

-0.00/+100.00 percent single section

Case Material:

Ceramic

Insulation Resistance At Reference Temp:

10000.0 megohms

Power Factor At Reference Temperature In Percent:

3.5000

Terminal Surface Treatment:

Solder

Terminal Type And Quantity:

1 tab, solder lug and 1 uninsulated wire lead

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A010b0