

View Online at <https://aerobasegroup.com/nsn/5910-01-069-0265>

Body Style:

Button type, w/thd mtg hole/stud

Reliability Indicator:

Not established

Terminal Length:

0.406 inches

Body Diameter:

1.125 inches

Body Length:

1.100 inches

Schematic Diagram Designator:

Electrod (s) grounded to case, w/gnd terminal

Anode Type:

Solid

Electrical Polarization:

Polarized

Mounting Facility Screw Thread Series Designator:

Unc

Mounting Facility Type And Quantity:

1 threaded mounting studs

Capacitance Value Per Section:

1000.000 microfarads single section

Nonderated Operating Temp:

Between -55.0 degrees celsius and 85.0 degrees celsius

Thread Size:

0.250 inches

Dc Leakage At Maximum Operating Temp:

195.0 microamperes

Nonderated Continuous Voltage Rating And Type Per Section:

40.0 dc single section

Tolerance Range Per Section:

-15.00/+50.00 percent single section

Case Material:

Metal

Capacitive Electrode Material:

Tantalum

Power Factor At Reference Tempurature In Percent:

75.0000

Equivalent Series Resistance At Reference Tempurature In Ohms:

1.50

Dc Leakage At Reference Temp:

25.000 microamperes

Terminal Type And Quantity:

1 solder stud and 1 tab, solder lug

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A010b0