## NSN 5910-01-069-6035



Ceramic Dielectric Fixed Capacitor - Page 1 of 2 View Online at https://aerobasegroup.com/nsn/5910-01-069-6035 **Body Style:** W/o mtg facilities terminal (s) on one surface **Reliability Indicator:** Not established **Terminal Length:** 1.500 inches **Body Length:** 0.100 inches **Body Width:** 0.100 inches **Body Height:** 0.100 inches Center To Center Distance Between Terminals Parallel To Length: 0.100 inches **Terminal Diameter:** 0.016 inches **Schematic Diagram Designator:** No common or grounded electrode (s) **Capacitance Value Per Section:** 2.700 picofarads single section **Nonderated Operating Temp:** Between -55.0 degrees celsius and 125.0 degrees celsius Tempurature Coefficient Of Capacitance Per Section In Ppm Per Deg Celsius: 0.0 single section Nonderated Continuous Voltage Rating And Type Per Section: 100.0 dc single section **Tolerance Of Tempurature Coefficient Per Section In Ppm Per Deg Celsius:** -120.0/+120.0 single section **Tolerance Range Per Section:** -0.10/+0.10 picofarads single section Case Material:

Tolerance Of Tempurature Coefficient Per Section In Ppm Per Deg Cels
-120.0/+120.0 single section
Tolerance Range Per Section:
-0.10/+0.10 picofarads single section
Case Material:
Plastic
Dissipation Factor At Reference Tempurature In Percent:
0.1000
Terminal Surface Treatment:
Solder
Terminal Type And Quantity:
2 uninsulated wire lead

Shelf Life:

N/a

**Unit Of Measure:** 

--

## NSN 5910-01-069-6035

Ceramic Dielectric Fixed Capacitor - Page 2 of 2



Demilitarization:

No

Fiig:

A010b0