

View Online at https://aerobasegroup.com/nsn/5910-01-070-1115

## **Body Style:**

W/o mtg facilities terminal (s) on one surface

### **Reliability Indicator:**

Not established

# **Terminal Length:**

1.125 inches

## **Body Length:**

0.290 inches

### **Body Width:**

0.290 inches

### **Body Height:**

### 0.090 inches

### Center To Center Distance Between Terminals Parallel To Length:

0.200 inches

### **Terminal Diameter:**

0.025 inches

## Schematic Diagram Designator:

No common or grounded electrode (s)

### **Capacitance Value Per Section:**

6800.000 picofarads single section

# Nonderated Operating Temp:

Between -55.0 degrees celsius and 125.0 degrees celsius

# Tempurature Coefficient Of Capacitance Per Section In Ppm Per Deg Celsius:

0.0 single section

# Nonderated Continuous Voltage Rating And Type Per Section:

50.0 dc single section

# Tolerance Of Tempurature Coefficient Per Section In Ppm Per Deg Celsius:

-30.0/+30.0 single section

### **Tolerance Range Per Section:**

-5.00/+5.00 percent single section

### **Case Material:**

Plastic

### Insulation Resistance At Reference Temp:

10000.0 megohms

# **Dissipation Factor At Reference Tempurature In Percent:**

## 0.0150

## **Test Data Document:**

81349-mil-c-20/36 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

### **Terminal Type And Quantity:**

2 uninsulated wire lead

Shelf Life:

N/a



Unit Of Measure:

---

Demilitarization:

No

Fiig:

A010b0