NSN 5910-01-070-7434

Paper-plastic Dielectric Metallized Fixed Capacitor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5910-01-070-7434

view Online at https://aerobasegroup.com/nsn/5910-01-070-7454
Body Style:
W/o mtg facilities, axial terminals
Reliability Indicator:
Established
Reliability Failure Rate Level In Percent:
1.0000
Terminal Length:
1.625 inches
Body Diameter:
0.574 inches
Body Length:
1.031 inches
Terminal Diameter:
0.032 inches
Schematic Diagram Designator:
No common or grounded electrode (s)
Insulation Resistance At Maximum Operating Temp:
700.0 megohm-microfarads
Capacitance Value Per Section:
1.000 microfarads single section
Nonderated Operating Temp:
Between -55.0 degrees celsius and 125.0 degrees celsius
Nonderated Continuous Voltage Rating And Type Per Section:
200.0 dc single section
Tolerance Range Per Section:
-5.00/+5.00 percent single section
Case Material:
Plastic
Insulation Resistance At Reference Temp:
100000.0 megohm-microfarads
Terminal Surface Treatment:
Solder
Test Data Document:
81349-mil-c-55514 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification
format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain
environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).
Terminal Type And Quantity:
2 uninsulated wire lead
Specification Data:
81349-mil-c-0055514/4 government specification
Shelf Life:

--

N/a

Unit Of Measure:

NSN 5910-01-070-7434

Paper-plastic Dielectric Metallized Fixed Capacitor - Page 2 of 2



_		••	• -				
1	em		ゖっ	riz	2†1	n	
_			ıιa	114	au	VII	١.

No

Fiig:

A010b0