## NSN 5910-01-072-2180

Electrolytic Fixed Capacitor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5910-01-072-2180

Body Style:
W/o mtg facilities, axial terminals
Mil-std-1276 Wire Lead Type Designator:
N-4
Reliability Indicator:
Established
Reliability Failure Rate Level In Percent:
1.0000
Terminal Length:
1.500 inches
Body Diameter:
0.289 inches
Body Length:
0.716 inches
Terminal Diameter:
0.250 inches
Schematic Diagram Designator:
Electrod (s) grounded to case, w/gnd terminal
Anode Type:
Solid
Electrical Polarization:
Polarized
Features Provided:
Hermetically sealed case
Capacitance Value Per Section:
18.000 microfarads single section
Nonderated Operating Temp:
85.0 degrees celsius
Nonderated Continuous Voltage Rating And Type Per Section:
50.0 dc single section
Tolerance Range Per Section:
-10.00/+10.00 percent single section
Case Material:
Metal
Capacitive Electrode Material:
Tantalum
Dissipation Factor At Reference Tempurature In Percent:
6.0000
Dc Leakage At Reference Temp:
4.500 microamperes
Case Insulation Material:

Plastic

## NSN 5910-01-072-2180

Electrolytic Fixed Capacitor - Page 2 of 2



Ī	erminal	Type	And	Quant	tity:

2 uninsulated wire lead

Shelf Life:

N/a

**Unit Of Measure:** 

--

Demilitarization:

No

Fiig:

A010b0