NSN 5910-01-072-3844

Ceramic Dielectric Fixed Capacitor - Page 1 of 2



| View Online at https://aerobasegroup.com/nsn/5910-01-072-3844 |
|--|
| Body Style: |
| W/o mtg facilities terminal (s) on one surface |
| Reliability Indicator: |
| Not established |
| Terminal Length: |
| 1.250 inches |
| Body Length: |
| 0.200 inches |
| Body Width: |
| 0.200 inches |
| Body Height: |
| 0.125 inches |
| Center To Center Distance Between Terminals Parallel To Length: |
| 0.100 inches |
| Terminal Diameter: |
| 0.020 inches |
| Schematic Diagram Designator: |
| No common or grounded electrode (s) |
| Capacitance Value Per Section: |
| 220.000 picofarads single section |
| Nonderated Operating Temp: |
| Between -55.0 degrees celsius and 125.0 degrees celsius |
| Tempurature Coefficient Of Capacitance Per Section In Ppm Per Deg Celsius: |
| 0.0 single section |
| Nonderated Continuous Voltage Rating And Type Per Section: |
| 100.0 dc single section |
| Tolerance Of Tempurature Coefficient Per Section In Ppm Per Deg Celsius: |
| -30.0/+30.0 single section |
| Tolerance Range Per Section: |
| -2.00/+2.00 percent single section |
| Case Material: |
| Plastic |
| Insulation Resistance At Reference Temp: |
| 2500.0 megohm-microfarads |
| Power Factor At Reference Tempurature In Percent: |
| 2.0000 |
| Terminal Surface Treatment: |
| Solder |
| Terminal Type And Quantity: |
| 2 uninsulated wire lead |

N/a

Shelf Life:

NSN 5910-01-072-3844

Ceramic Dielectric Fixed Capacitor - Page 2 of 2



| | | • • | | | |
|---|----|-----|-------------|----------|--|
| ш | ın | 10 | <i>(</i>)+ | Measure: | |
| | | | | | |

--

Demilitarization:

No

Fiig:

A010b0