

View Online at <https://aerobasegroup.com/nsn/5910-01-072-3852>

Body Style:

W/o mtg facilities, axial terminals

Reliability Indicator:

Not established

Terminal Length:

1.500 inches

Body Diameter:

0.650 inches

Body Length:

1.462 inches

Terminal Diameter:

0.025 inches

Schematic Diagram Designator:

Electrod (s) grounded to case, w/gnd terminal

Anode Type:

Plain foil

Electrical Polarization:

Polarized

End Application:

Forrestal class cv; virginia class cgn (41); los angeles class ssn (688); spruance class dd (963); ticonderoga class cg (47); landing craft air cushion (lcac); kidd class ddg; nimitz class cvn; sturgeon class ssn (637)

Features Provided:

Hermetically sealed case

Capacitance Value Per Section:

1000.000 microfarads single section

Nonderated Operating Temp:

Between -55.0 degrees celsius and 105.0 degrees celsius

Nonderated Continuous Voltage Rating And Type Per Section:

12.0 dc single section

Criticality Code Justification:

Feat

Tolerance Range Per Section:

-10.00/+100.00 percent single section

Case Material:

Metal

Capacitive Electrode Material:

Aluminum

Terminal Surface Treatment:

Solder

Case Insulation Material:

Plastic

Special Features:

Weapon system essential

Terminal Type And Quantity:

2 uninsulated wire lead

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A010b0