NSN 5910-01-073-4561

Body Style:

Paper Dielectric Fixed Capacitor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5910-01-073-4561

| W/thd mtg hol (s)/stud(s) terminal(s) on one surface | |
|--|--|
| Reliability Indicator: | |
| Not established | |
| Terminal Length: | |
| 1.750 inches | |
| Body Length: | |
| 1.625 inches | |
| Body Width: | |
| 0.562 inches | |
| Body Height: | |
| 1.775 inches | |
| Center To Center Distance Between Terminals Parallel To Length: | |
| 0.625 inches | |
| Terminal Diameter: | |
| 0.032 inches | |
| Distance Between Centerlines Of Mounting Facilities Parallel To Body Length: | |
| 1.375 inches | |
| Schematic Diagram Designator: | |
| No common or grounded electrode (s) | |
| Mounting Facility Screw Thread Series Designator: | |
| Unc | |
| Mounting Facility Type And Quantity: | |
| 2 threaded mounting studs | |
| Features Provided: | |
| Hermetically sealed case | |
| Capacitance Value Per Section: | |
| 0.220 microfarads single section | |
| Nonderated Operating Temp: | |
| Between -55.0 degrees celsius and 85.0 degrees celsius | |
| Thread Size: | |
| 0.138 inches | |
| Nonderated Continuous Voltage Rating And Type Per Section: | |
| 900.0 dc single section | |
| Tolerance Range Per Section: | |
| -10.00 to 10.00 percent single section | |
| Case Material: | |
| Metal | |
| Terminal Surface Treatment: | |
| Soldar | |

2 uninsulated wire lead

Terminal Type And Quantity:

NSN 5910-01-073-4561

Paper Dielectric Fixed Capacitor - Page 2 of 2



| _ | | | | | |
|----|----|----|-----|------|--|
| C. | ~~ | 14 | I i | ife: | |
| J. | 16 | | | HE. | |

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A010b0