NSN 5910-01-076-1888 Glass Dielectric Variable Capacitor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5910-01-076-1888
Body Style:
Piston
Overall Length:
0.700 inches
Terminal Length:
0.750 inches
Body Length:
0.600 inches
Overall Diameter:
0.312 inches
Tempurature Coefficient Of Capacitance Range In Ppm Per Deg Celsius:
-50.0/+50.0 single section
Center To Center Distance Between Terminals Parallel To Length:
0.450 inches
Center To Center Distance Between Terminals Parallel To Diameter:
0.200 inches
Terminal Diameter:
0.040 inches
Center To Center Distance Between Mounting Facilities Parallel To Diameter:
0.200 inches
Distance Between Centerlines Of Mounting Facilities Parallel To Body Length:
0.450 inches
Inclosure Type:
Encased
Adjustment Device Torque:
Between 1.000 inch-ounces and 5.000 inch-ounces
Mounting Facility Type And Quantity:
4 terminal
Nonderated Operating Temp:
Between -55.0 degrees celsius and 125.0 degrees celsius
Capacitance Range In Picofarads:
+1.0/+8.5 single section
Nonderated Voltage Rating And Type:
1000.0 dc continuous single section
Adjustment Device Drive Type And Quantity:
1 slotted screw
Terminal Type And Quantity:
4 printed circuit
Shelf Life:
N/a
Unit Of Measure:

NSN 5910-01-076-1888

Glass Dielectric Variable Capacitor - Page 2 of 2



Demilitarization:

No

Fiig:

A096a0