## NSN 5910-01-076-7623

Plastic Dielectric Fixed Capacitor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5910-01-076-7623 **Body Style:** W/o mtg facilities, radial terminals **Reliability Indicator:** Not established **Terminal Length:** 1.250 inches **Body Diameter:** 0.400 inches **Body Length:** 0.750 inches **Center To Center Distance Between Terminals Parallel To Length:** 0.375 inches **Terminal Diameter:** 0.032 inches **Schematic Diagram Designator:** No common or grounded electrode (s) **Internal Electrical Connection Type:** Extended foil **Insulation Resistance At Maximum Operating Temp:** 2500.0 megohm-microfarads **Capacitance Value Per Section:** 0.010 microfarads single section **Nonderated Operating Temp:** Between -55.0 degrees celsius and 85.0 degrees celsius Tempurature Coefficient Of Capacitance Per Section In Ppm Per Deg Celsius: 0.0 single section Nonderated Continuous Voltage Rating And Type Per Section: 400.0 dc single section Tolerance Of Tempurature Coefficient Per Section In Ppm Per Deg Celsius: -180.0/+180.0 single section **Tolerance Range Per Section:** -5.00/+5.00 percent single section **Case Material:** Plastic **Insulation Resistance At Reference Temp:** 50000.0 megohm-microfarads **Dissipation Factor At Reference Tempurature In Percent:** 0.1000 **Terminal Surface Treatment:** Solder

**Dielectric Material:** 

Plastic polyethylene terephthalate

## NSN 5910-01-076-7623

Plastic Dielectric Fixed Capacitor - Page 2 of 2



Special Features:
Crimped leads
Terminal Type And Quantity:
2 uninsulated wire lead
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No

Fiig: A010b0