

View Online at https://aerobasegroup.com/nsn/5910-01-077-2578

# **Body Style:**

W/o mtg facilities, terminals on opposite surfaces

## **Reliability Indicator:**

Established

# **Reliability Failure Rate Level In Percent:**

0.0100

#### **Terminal Length:**

1.250 inches

#### **Body Length:**

0.205 inches

#### **Body Width:**

0.090 inches

## Body Height:

0.100 inches

#### **Terminal Diameter:**

0.016 inches

# Schematic Diagram Designator:

No common or grounded electrode (s)

#### **Features Provided:**

Hermetically sealed case

## Capacitance Value Per Section:

1200.000 picofarads single section

## Nonderated Operating Temp:

Between -55.0 degrees celsius and 125.0 degrees celsius

# Tempurature Coefficient Of Capacitance Per Section In Ppm Per Deg Celsius:

0.0 single section

## Nonderated Continuous Voltage Rating And Type Per Section:

50.0 dc single section

## Tolerance Of Tempurature Coefficient Per Section In Ppm Per Deg Celsius:

-30.0/+30.0 single section

## **Tolerance Range Per Section:**

-2.00/+2.00 percent single section

#### **Case Material:**

Plastic

## Insulation Resistance At Reference Temp:

100000.0 megohms

# **Dissipation Factor At Reference Tempurature In Percent:**

0.1500

# Test Data Document:

96682-sc5281001 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing,

etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing)

# Terminal Type And Quantity:

2 uninsulated wire lead



Shelf Life:

N/a

Unit Of Measure:

---

Demilitarization:

No

Fiig:

A010b0