

View Online at <https://aerobasegroup.com/nsn/5910-01-077-2590>

**Body Style:**

W/o mtg facilities, terminals on opposite surfaces

**Mil-std-1276 Wire Lead Type Designator:**

N-1

**Reliability Indicator:**

Not established

**Terminal Length:**

0.090 inches

**Body Length:**

0.320 inches

**Body Width:**

0.100 inches

**Body Height:**

0.180 inches

**Schematic Diagram Designator:**

No common or grounded electrode (s)

**Anode Type:**

Solid

**Impedance At Minimum Operating Temperature In Ohms:**

0.22

**Electrical Polarization:**

Polarized

**Capacitance Value Per Section:**

8.000 microfarads single section

**Nonderated Operating Temp:**

Between -55.0 degrees celsius and 85.0 degrees celsius

**Nonderated Continuous Voltage Rating And Type Per Section:**

10.0 dc single section

**Tolerance Range Per Section:**

-10.00/+10.00 percent single section

**Case Material:**

Plastic

**Capacitive Electrode Material:**

Tantalum

**Dissipation Factor At Reference Temperature In Percent:**

6.0000

**Dc Leakage At Reference Temp:**

1.800 microamperes

**Special Features:**

Burn-in

**Terminal Type And Quantity:**

2 tab, solder lug

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A010b0