## NSN 5910-01-077-7112

**Body Style:** 

N/a

Paper-plastic Dielectric Metallized Fixed Capacitor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5910-01-077-7112

W/o mtg facilities terminal (s) on one surface				
Reliability Indicator:				
Established				
Reliability Failure Rate Level In Percent:				
1.0000				
Terminal Length:				
1.000 inches				
Body Length:				
0.550 inches				
Body Width:				
0.440 inches				
Body Height:				
0.300 inches				
Center To Center Distance Between Terminals Parallel To Length:				
0.400 inches				
Terminal Diameter:				
0.025 inches				
Schematic Diagram Designator:				
No common or grounded electrode (s)				
Insulation Resistance At Maximum Operating Temp:				
1000.0 megohms				
Capacitance Value Per Section:				
0.220 microfarads single section				
Nonderated Operating Temp:				
Between -55.0 degrees celsius and 125.0 degrees celsius				
Nonderated Continuous Voltage Rating And Type Per Section:				
100.0 dc single section				
Tolerance Range Per Section:				
-2.00/+2.00 microfarads single section				
Case Material:				
Plastic				
Insulation Resistance At Reference Temp:				
100000.0 megohms				
Dissipation Factor At Reference Tempurature In Percent:				
0.5000				
Terminal Surface Treatment:				
Solder				
Terminal Type And Quantity:				
2 uninsulated wire lead				
Shelf Life:				

## NSN 5910-01-077-7112

Paper-plastic Dielectric Metallized Fixed Capacitor - Page 2 of 2



		• -		
	In	11	<i>(</i> )+	Measure:
v	,,,		$\mathbf{v}$	wicasui c.

--

Demilitarization:

No

Fiig:

A010b0