

View Online at <https://aerobasegroup.com/nsn/5910-01-077-7556>

Body Style:

Rotary

Terminal Length:

Between 0.235 inches and 0.265 inches

Overall Height:

Between 0.130 inches and 0.178 inches

Overall Diameter:

Between 0.203 inches and 0.233 inches

Center To Center Distance Between Terminals Parallel To Diameter:

Between 0.180 inches and 0.210 inches

Quality Factor At 25 Deg Celsius:

500.0

Fragility Factor:

Moderately rugged

Terminal Width:

0.040 inches

Terminal Thickness:

0.008 inches

Inclosure Type:

Encapsulated

Adjustment Device Torque:

Between 0.500 inch-ounces and 3.000 inch-ounces

Insulation Dc Resistance At 25 Deg Celsius:

10000.0 megohms

Mounting Facility Type And Quantity:

2 terminal

Nonderated Operating Temp:

Between -55.0 degrees celsius and 85.0 degrees celsius

Capacitance Range In Picofarads:

+3.5/+20.0 single section

Nonderated Voltage Rating And Type:

100.0 dc continuous single section

Capacitance Change In Percent At Operating Temperature From 25 Deg Celsius:

-4.50/+2.00 single section and -2.50/+2.00 single section

Adjustment Device Drive Type And Quantity:

1 slotted screw

Material:

Steatite base

Precious Material And Location:

Electrodes silver

Precious Material:

Silver

Terminal Type And Quantity:

2 tab, solder lug

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A096a0