

View Online at https://aerobasegroup.com/nsn/5910-01-078-8058

## **Body Style:**

W/o mtg facilities, axial terminals

**Reliability Indicator:** 

Established

**Reliability Failure Rate Level In Percent:** 

1.0000

**Terminal Length:** 

1.625 inches

**Body Diameter:** 

0.235 inches

**Body Length:** 

0.813 inches

**Terminal Diameter:** 

0.025 inches

Schematic Diagram Designator:

No common or grounded electrode (s)

**Features Provided:** 

Hermetically sealed case

**Capacitance Value Per Section:** 

0.068 microfarads single section

## Nonderated Operating Temp:

Between -65.0 degrees celsius and 125.0 degrees celsius

## Nonderated Continuous Voltage Rating And Type Per Section:

100.0 dc single section

#### **Tolerance Range Per Section:**

-2.00/+2.00 percent single section

#### **Case Material:**

Metal

Insulation Resistance At Reference Temp:

10000.0 megohms

## **Dissipation Factor At Reference Tempurature In Percent:**

0.1500

**Case Insulation Material:** 

Plastic

# Test Data Document:

81349-mil-c-83421/1 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain

environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

# Terminal Type And Quantity:

2 uninsulated wire lead

Shelf Life:

N/a



Demilitarization:

No

Fiig:

A010b0