## NSN 5910-01-079-0320

Electrolytic Fixed Capacitor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5910-01-079-0320 **Body Style:** W/o mtg facilities, terminal (s) on one end Reliability Indicator: Not established **Terminal Length:** 0.250 inches **Body Diameter:** 3.078 inches **Body Length:** 5.750 inches **Center To Center Distance Between Terminals Parallel To Diameter:** 1.250 inches **Terminal Diameter:** 0.190 inches **Schematic Diagram Designator:** No common or grounded electrode (s) **Anode Type:** Plain foil **Electrical Polarization:** Polarized **Capacitance Value Per Section:** 4500.000 microfarads single section **Nonderated Operating Temp:** Between -40.0 degrees celsius and 85.0 degrees celsius Dc Leakage At Maximum Operating Temp: 15.0 milliamperes Nonderated Continuous Voltage Rating And Type Per Section: 250.0 dc single section **Tolerance Range Per Section:** -10.00/+50.00 percent single section Case Material: Metal **Capacitive Electrode Material:** Aluminum **Equivalent Series Resistance At Reference Tempurature In Ohms:** Dc Leakage At Reference Temp: 6.000 milliamperes **Case Insulation Material:** 

**Plastic Terminal Type And Quantity:** 2 threaded hole

## NSN 5910-01-079-0320

Electrolytic Fixed Capacitor - Page 2 of 2



| _ |    |      |   |        |  |
|---|----|------|---|--------|--|
| c | hο | JIF. |   | .ife:  |  |
| J |    |      | _ | .II C. |  |

N/a

**Unit Of Measure:** 

--

Demilitarization:

No

Fiig:

A010b0