NSN 5910-01-079-0326

Paper-plastic Dielectric Metallized Fixed Capacitor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5910-01-079-0326

Body Style:
W/o mtg facilities, axial terminals
Reliability Indicator:
Not established
Terminal Length:
1.625 inches
Body Diameter:
Between 0.312 inches and 0.332 inches
Body Length:
Between 0.657 inches and 0.717 inches
Terminal Diameter:
0.025 inches
Schematic Diagram Designator:
No common or grounded electrode (s)
Features Provided:
Hermetically sealed case
Insulation Resistance At Maximum Operating Temp:
250000.0 megohm-microfarads
Capacitance Value Per Section:
0.020 microfarads single section
Nonderated Operating Temp:
Between -62.0 degrees celsius and 125.0 degrees celsius
Nonderated Continuous Voltage Rating And Type Per Section:
50.0 dc single section
Tolerance Range Per Section:
-1.00/+1.00 percent single section
Case Material:
Case Material: Metal
Metal
Metal Insulation Resistance At Reference Temp:
Metal Insulation Resistance At Reference Temp: 5000000.0 megohm-microfarads
Metal Insulation Resistance At Reference Temp: 5000000.0 megohm-microfarads Dissipation Factor At Reference Tempurature In Percent:
Metal Insulation Resistance At Reference Temp: 5000000.0 megohm-microfarads Dissipation Factor At Reference Tempurature In Percent: 0.0300
Metal Insulation Resistance At Reference Temp: 5000000.0 megohm-microfarads Dissipation Factor At Reference Tempurature In Percent: 0.0300 Terminal Surface Treatment:
Metal Insulation Resistance At Reference Temp: 5000000.0 megohm-microfarads Dissipation Factor At Reference Tempurature In Percent: 0.0300 Terminal Surface Treatment: Solder
Metal Insulation Resistance At Reference Temp: 5000000.0 megohm-microfarads Dissipation Factor At Reference Tempurature In Percent: 0.0300 Terminal Surface Treatment: Solder Case Insulation Material:
Metal Insulation Resistance At Reference Temp: 5000000.0 megohm-microfarads Dissipation Factor At Reference Tempurature In Percent: 0.0300 Terminal Surface Treatment: Solder Case Insulation Material: Plastic
Metal Insulation Resistance At Reference Temp: 5000000.0 megohm-microfarads Dissipation Factor At Reference Tempurature In Percent: 0.0300 Terminal Surface Treatment: Solder Case Insulation Material: Plastic Terminal Type And Quantity:
Metal Insulation Resistance At Reference Temp: 5000000.0 megohm-microfarads Dissipation Factor At Reference Tempurature In Percent: 0.0300 Terminal Surface Treatment: Solder Case Insulation Material: Plastic Terminal Type And Quantity: 2 uninsulated wire lead

--

NSN 5910-01-079-0326

Paper-plastic Dielectric Metallized Fixed Capacitor - Page 2 of 2



	tariz	

No

Fiig:

A010b0