

View Online at https://aerobasegroup.com/nsn/5910-01-079-6733

### Body Style:

W/thd bushing mtg, terminals on opposite end

### **Reliability Indicator:**

Not established

## Width Across Flats:

Between 0.182 inches and 0.192 inches

#### **Terminal Length:**

0.610 inches

#### **Body Length:**

Between 0.458 inches and 0.478 inches

### **Continuous Current Rating In Amps:**

10.0

**Terminal Diameter:** 

0.032 inches

### Schematic Diagram Designator:

Feedthrough

**End Application:** 

1270-01-072-4555headsup display

## Mounting Facility Screw Thread Series Designator:

Unef

### Mounting Facility Type And Quantity:

1 threaded bushing

# Features Provided:

Mounting hardware

### Capacitance Value Per Section:

0.100 microfarads single section

### Voltage Tempurature Limits Per Section In Percent Capacitance Change:

-55.0/+125.0 with rated voltage applied single section

### Nonderated Operating Temp:

25.0 degrees celsius

### Thread Size:

0.216 inches

### Nonderated Continuous Voltage Rating And Type Per Section:

200.0 dc single section

### **Tolerance Range Per Section:**

-0.00/+100.00 percent single section

### Case Material:

Metal

### **Terminal Type And Quantity:**

2 uninsulated wire lead

#### Shelf Life:

N/a



Unit Of Measure:

--

Demilitarization:

No

Fiig:

A010b0