

View Online at https://aerobasegroup.com/nsn/5910-01-079-6803

#### **Body Style:**

W/o mtg facilities terminal (s) on one surface

**Reliability Indicator:** 

Not established

## **Terminal Length:**

1.500 inches

### **Body Length:**

0.180 inches

#### **Body Width:**

0.180 inches

#### **Body Height:**

0.100 inches

### Center To Center Distance Between Terminals Parallel To Length:

0.100 inches

#### **Terminal Diameter:**

0.020 inches

#### Schematic Diagram Designator:

No common or grounded electrode (s)

#### **Capacitance Value Per Section:**

10000.000 picofarads single section

## Voltage Tempurature Limits Per Section In Percent Capacitance Change:

-15.0/+15.0 without voltage applied single section

## Nonderated Operating Temp:

Between -55.0 degrees celsius and 125.0 degrees celsius

### Nonderated Continuous Voltage Rating And Type Per Section:

100.0 dc single section

### **Tolerance Range Per Section:**

-20.00/+20.00 percent single section

#### **Case Material:**

Ceramic

# Insulation Resistance At Reference Temp:

100000.0 megohms

# Dissipation Factor At Reference Tempurature In Percent:

2.5000

# Test Data Document:

81349-mil-c-11015/24 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain

environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

## Terminal Type And Quantity:

2 uninsulated wire lead

## Shelf Life:

N/a

Unit Of Measure:



Demilitarization:

No

Fiig:

A010b0