

View Online at https://aerobasegroup.com/nsn/5910-01-080-0702

| De de Otoleo |
|---|
| Body Style: |
| Chip type |
| Reliability Indicator: Not established |
| |
| Body Length: |
| 0.130 inches |
| Body Width: |
| 0.110 inches |
| Body Height: |
| 0.100 inches |
| Schematic Diagram Designator: |
| No common or grounded electrode (s) |
| Capacitance Value Per Section: |
| 0.010 microfarads single section |
| Voltage Tempurature Limits Per Section In Percent Capacitance Change: |
| -15.0/+15.0 without voltage applied single section |
| Nonderated Operating Temp: |
| Between -55.0 degrees celsius and 125.0 degrees celsius |
| Nonderated Continuous Voltage Rating And Type Per Section: |
| 50.0 dc single section |
| Tolerance Range Per Section: |
| -2.00/+2.00 percent single section |
| Case Material: |
| |
| Insulation Resistance At Reference Temp: |
| 10000.0 megohms Dissipation Factor At Reference Tempurature In Percent: |
| 2.5000 |
| Z.5000 Terminal Surface Treatment: |
| Solder |
| Precious Material And Location: |
| Terminals silver and terminals gold |
| Terminal Type And Quantity: |
| 2 bonding pad |
| Shelf Life: |
| N/a |
| Unit Of Measure: |
| |
| Demilitarization: |
| No |
| Filg: |
| A010b0 |
| |