

View Online at <https://aerobasegroup.com/nsn/5910-01-081-0763>

**Body Style:**

W/thd mtg hol (s)/stud(s) terminal(s) on one surface

**Reliability Indicator:**

Not established

**Terminal Length:**

Between 0.230 inches and 0.270 inches

**Body Length:**

Between 1.820 inches and 1.860 inches

**Body Width:**

1.600 inches

**Body Height:**

Between 1.340 inches and 1.380 inches

**Continuous Current Rating In Amps:**

2.9

**Center To Center Distance Between Terminals Parallel To Length:**

Between 1.641 inches and 1.765 inches

**Terminal Height From Body:**

Between 0.186 inches and 0.207 inches

**Schematic Diagram Designator:**

No common or grounded electrode (s)

**Electrical Polarization:**

Polarized

**Mounting Facility Screw Thread Series Designator:**

Unc

**Mounting Facility Type And Quantity:**

2 threaded mounting holes

**Section Quantity:**

2

**Capacitance Value Per Section:**

1990.000 microfarads all sections

**Nonderated Operating Temp:**

Between -55.0 degrees celsius and 105.0 degrees celsius

**Thread Size:**

0.138 inches

**Nonderated Continuous Voltage Rating And Type Per Section:**

12.0 dc all sections

**Tolerance Range Per Section:**

-0.00/+110.00 microfarads all sections

**Case Material:**

Metal

**Capacitive Electrode Material:**

Aluminum

**Equivalent Series Resistance At Reference Temperature In Ohms:**

0.06

**Dc Leakage At Reference Temp:**

75.000 microamperes

**Terminal Type And Quantity:**

8 tab, solder lug

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A010b0