

View Online at https://aerobasegroup.com/nsn/5910-01-081-3122

## **Body Style:**

W/o mtg facilities terminal (s) on one surface

## **Reliability Indicator:**

Not established

# **Terminal Length:**

0.750 inches

# **Body Length:**

0.080 inches

#### **Body Width:**

0.090 inches

### **Body Height:**

### 0.045 inches

## Center To Center Distance Between Terminals Parallel To Length:

0.100 inches

#### **Terminal Diameter:**

0.016 inches

# Schematic Diagram Designator:

No common or grounded electrode (s)

## Capacitance Value Per Section:

33.000 picofarads single section

# Voltage Tempurature Limits Per Section In Percent Capacitance Change:

-15.0/+15.0 without voltage applied single section

# Nonderated Operating Temp:

Between -55.0 degrees celsius and 125.0 degrees celsius

### Nonderated Continuous Voltage Rating And Type Per Section:

100.0 dc single section

### **Tolerance Range Per Section:**

-10.00/+10.00 percent single section

### **Case Material:**

Ceramic

### Insulation Resistance At Reference Temp:

100000.0 megohms

### **Dissipation Factor At Reference Tempurature In Percent:**

2.5000

### Test Data Document:

81349-mil-c-11015/24 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain

environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

# **Terminal Type And Quantity:**

2 uninsulated wire lead

## Shelf Life:

N/a

Unit Of Measure:



Demilitarization:

No

Fiig:

A010b0