NSN 5910-01-081-3460

Plastic Dielectric Fixed Capacitor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5910-01-081-3460

ı	Body Style:
١	W/o mtg facilities, axial terminals
ı	Reliability Indicator:
1	Not established
1	Terminal Length:
•	1.625 inches
E	Body Diameter:
(0.670 inches
ı	Body Length:
•	1.688 inches
1	Terminal Diameter:
(0.032 inches
,	Schematic Diagram Designator:
1	No common or grounded electrode (s)
ı	nternal Electrical Connection Type:
E	Extended foil
ı	Features Provided:
ŀ	Hermetically sealed case
ı	Insulation Resistance At Maximum Operating Temp:
2	20.0 megohm-microfarads
(Capacitance Value Per Section:
(0.150 microfarads single section
ı	Nonderated Operating Temp:
	Between -65.0 degrees celsius and 125.0 degrees celsius
	Nonderated Continuous Voltage Rating And Type Per Section:
	1000.0 dc single section
	Tolerance Range Per Section:
	-10.00/+10.00 percent single section
	Case Material:
	Metal
	Insulation Resistance At Reference Temp:
	25000.0 megohms
	Dissipation Factor At Reference Tempurature In Percent:
	1.0000
	Terminal Surface Treatment:
	Solder
	Dielectric Material:
	Paper and plastic polyethylene terephthalate
	Case Insulation Material:
	Plastic
1	Test Data Document:

81349-mil-c-19978 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

NSN 5910-01-081-3460

Plastic Dielectric Fixed Capacitor - Page 2 of 2



Terminal Type And Quantity:		
2 uninsulated wire lead		
Specification Data:		
81349-mil-c-19978/19a government specification		
Shelf Life:		
N/a		
Unit Of Measure:		
Demilitarization:		
No		

Fiig: A010b0