NSN 5910-01-081-3676

Ceramic Dielectric Fixed Capacitor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5910-01-081-3676

| view Online at https://aerobasegroup.com/hist//3310-01-001-3070 |
|--|
| Body Style: |
| W/o mtg facilities, axial terminals |
| Reliability Indicator: |
| Established |
| Reliability Failure Rate Level In Percent: |
| 1.0000 |
| Terminal Length: |
| 1.500 inches |
| Body Diameter: |
| 0.140 inches |
| Body Length: |
| 0.390 inches |
| Terminal Diameter: |
| 0.025 inches |
| Schematic Diagram Designator: |
| No common or grounded electrode (s) |
| Capacitance Value Per Section: |
| 0.068 microfarads single section |
| Voltage Tempurature Limits Per Section In Percent Capacitance Change: |
| -25.0/+15.0 with rated voltage applied single section |
| Nonderated Operating Temp: |
| Between -55.0 degrees celsius and 125.0 degrees celsius |
| Nonderated Continuous Voltage Rating And Type Per Section: |
| 50.0 dc single section |
| Tolerance Range Per Section: |
| -20.00/+20.00 percent single section |
| Case Material: |
| Plastic |
| Insulation Resistance At Reference Temp: |
| 100000.0 megohms |
| Dissipation Factor At Reference Tempurature In Percent: |
| 2.5000 |
| Test Data Document: |
| 81349-mil-c-39014/5 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification |
| format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain |
| environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). |
| Terminal Type And Quantity: |
| 2 uninsulated wire lead |
| Shelf Life: |
| N/a |
| Unit Of Measure: |
| |
| Demilitarization: |

No

NSN 5910-01-081-3676

Ceramic Dielectric Fixed Capacitor - Page 2 of 2



Fiig:

A010b0