Paper-plastic Dielectric Metallized Fixed Capacitor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5910-01-081-5450

## Body Style:

W/o mtg facilities terminal (s) on one surface

**Reliability Indicator:** 

Not established

Terminal Length:

6.0 millimeters

#### Body Length:

10.5 millimeters

#### **Body Width:**

8.5 millimeters

#### **Body Height:**

4.0 millimeters

## Center To Center Distance Between Terminals Parallel To Length:

7.5 millimeters

#### **Terminal Diameter:**

0.7 millimeters

## Schematic Diagram Designator:

No common or grounded electrode (s)

#### **Capacitance Value Per Section:**

0.100 microfarads single section

### Nonderated Operating Temp:

Between -40.0 degrees celsius and 100.0 degrees celsius

### Nonderated Continuous Voltage Rating And Type Per Section:

63.0 ac-rms single section and 100.0 dc single section

#### **Tolerance Range Per Section:**

-10.00/+10.00 percent single section

#### **Case Material:**

Plastic

#### Insulation Resistance At Reference Temp:

30000.0 megohms

# Dissipation Factor At Reference Tempurature In Percent:

0.020

# **Terminal Surface Treatment:**

Solder

# Terminal Type And Quantity:

2 uninsulated wire lead

Shelf Life:

N/a

Unit Of Measure:

--

# Demilitarization:

No

# NSN 5910-01-081-5450

Paper-plastic Dielectric Metallized Fixed Capacitor - Page 2 of 2

**Fiig:** A010b0

