Plastic Dielectric Fixed Capacitor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5910-01-083-1601

## **Body Style:**

W/o mtg facilities, axial terminals

## **Reliability Indicator:**

Established

## **Reliability Failure Rate Level In Percent:**

1.0000

## **Terminal Length:**

1.625 inches

## **Body Diameter:**

0.400 inches

## **Body Length:**

1.125 inches

## **Terminal Diameter:**

0.032 inches

## Schematic Diagram Designator:

No common or grounded electrode (s)

## **Features Provided:**

Hermetically sealed case

## **Capacitance Value Per Section:**

0.100 microfarads single section

## Nonderated Operating Temp:

Between -65.0 degrees celsius and 125.0 degrees celsius

## Nonderated Continuous Voltage Rating And Type Per Section:

200.0 dc single section

## **Tolerance Range Per Section:**

-10.00/+10.00 percent single section

## **Case Material:**

Metal

## **Dissipation Factor At Reference Tempurature In Percent:**

1.0000

## **Case Insulation Material:**

Plastic

# Test Data Document:

81349-mil-c-19978/9 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

# Terminal Type And Quantity:

2 uninsulated wire lead

Shelf Life:

N/a

Unit Of Measure:

---

Demilitarization:

No

# NSN 5910-01-083-1601

Plastic Dielectric Fixed Capacitor - Page 2 of 2

**Fiig:** A010b0

