NSN 5910-01-084-2292

Paper-plastic Dielectric Metallized Fixed Capacitor - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5910-01-084-2292

Body Style:
W/o mtg facilities, terminals on opposite surfaces
Reliability Indicator:
Not established
Terminal Length:
1.867 inches
Body Length:
1.102 inches
Body Width:
0.335 inches
Body Height:
0.512 inches
Terminal Diameter:
0.023 inches
Schematic Diagram Designator:
No common or grounded electrode (s)
Capacitance Value Per Section:
0.100 microfarads single section
Nonderated Operating Temp:
125.0 degrees celsius
Nonderated Continuous Voltage Rating And Type Per Section:
Nonderated Continuous Voltage Rating And Type Per Section: 630.0 dc single section
630.0 dc single section
630.0 dc single section Tolerance Range Per Section:
630.0 dc single section Tolerance Range Per Section: -20.00/+20.00 percent single section
630.0 dc single section Tolerance Range Per Section: -20.00/+20.00 percent single section Case Material:
630.0 dc single section Tolerance Range Per Section: -20.00/+20.00 percent single section Case Material: Plastic
630.0 dc single section Tolerance Range Per Section: -20.00/+20.00 percent single section Case Material: Plastic Terminal Surface Treatment:
630.0 dc single section Tolerance Range Per Section: -20.00/+20.00 percent single section Case Material: Plastic Terminal Surface Treatment: Solder
630.0 dc single section Tolerance Range Per Section: -20.00/+20.00 percent single section Case Material: Plastic Terminal Surface Treatment: Solder Dielectric Material:
630.0 dc single section Tolerance Range Per Section: -20.00/+20.00 percent single section Case Material: Plastic Terminal Surface Treatment: Solder Dielectric Material: Plastic
630.0 dc single section Tolerance Range Per Section: -20.00/+20.00 percent single section Case Material: Plastic Terminal Surface Treatment: Solder Dielectric Material: Plastic Terminal Type And Quantity:
630.0 dc single section Tolerance Range Per Section: -20.00/+20.00 percent single section Case Material: Plastic Terminal Surface Treatment: Solder Dielectric Material: Plastic Terminal Type And Quantity: 2 uninsulated wire lead
630.0 dc single section Tolerance Range Per Section: -20.00/+20.00 percent single section Case Material: Plastic Terminal Surface Treatment: Solder Dielectric Material: Plastic Terminal Type And Quantity: 2 uninsulated wire lead Shelf Life:
630.0 dc single section Tolerance Range Per Section: -20.00/+20.00 percent single section Case Material: Plastic Terminal Surface Treatment: Solder Dielectric Material: Plastic Terminal Type And Quantity: 2 uninsulated wire lead Shelf Life: N/a
630.0 dc single section Tolerance Range Per Section: -20.00/+20.00 percent single section Case Material: Plastic Terminal Surface Treatment: Solder Dielectric Material: Plastic Terminal Type And Quantity: 2 uninsulated wire lead Shelf Life: N/a
630.0 dc single section Tolerance Range Per Section: -20.00/+20.00 percent single section Case Material: Plastic Terminal Surface Treatment: Solder Dielectric Material: Plastic Terminal Type And Quantity: 2 uninsulated wire lead Shelf Life: N/a Unit Of Measure:
630.0 dc single section Tolerance Range Per Section: -20.00/+20.00 percent single section Case Material: Plastic Terminal Surface Treatment: Solder Dielectric Material: Plastic Terminal Type And Quantity: 2 uninsulated wire lead Shelf Life: N/a Unit Of Measure: Demilitarization: