

View Online at <https://aerobasegroup.com/nsn/5910-01-085-2188>

Body Style:

Dual inline

Reliability Indicator:

Not established

Terminal Length:

1.000 inches

Body Length:

0.200 inches

Body Width:

Between 0.240 inches and 0.280 inches

Body Height:

0.180 inches

Center To Center Distance Between Terminals Parallel To Length:

0.100 inches

Terminal Diameter:

Between 0.015 inches and 0.023 inches

Schematic Diagram Designator:

Two common terminals for each electrode

Anode Type:

Solid

Impedance At Minimum Operating Temperature In Ohms:

1.0

Electrical Polarization:

Polarized

Section Quantity:

2

Capacitance Value Per Section:

33.000 microfarads all sections

Nonderated Operating Temp:

Between -55.0 degrees celsius and 85.0 degrees celsius

Dc Leakage At Maximum Operating Temp:

8.0 microamperes

Nonderated Continuous Voltage Rating And Type Per Section:

10.0 dc all sections

Tolerance Range Per Section:

-10.00/+10.00 percent all sections

Case Material:

Plastic

Capacitive Electrode Material:

Tantalum

Dissipation Factor At Reference Temperature In Percent:

6.0000

Dc Leakage At Reference Temp:

0.020 microamperes

Terminal Surface Treatment:

Solder

Terminal Type And Quantity:

4 uninsulated wire lead

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A010b0