

View Online at <https://aerobasegroup.com/nsn/5910-01-085-2188>

**Body Style:**

Dual inline

**Reliability Indicator:**

Not established

**Terminal Length:**

1.000 inches

**Body Length:**

0.200 inches

**Body Width:**

Between 0.240 inches and 0.280 inches

**Body Height:**

0.180 inches

**Center To Center Distance Between Terminals Parallel To Length:**

0.100 inches

**Terminal Diameter:**

Between 0.015 inches and 0.023 inches

**Schematic Diagram Designator:**

Two common terminals for each electrode

**Anode Type:**

Solid

**Impedance At Minimum Operating Temperature In Ohms:**

1.0

**Electrical Polarization:**

Polarized

**Section Quantity:**

2

**Capacitance Value Per Section:**

33.000 microfarads all sections

**Nonderated Operating Temp:**

Between -55.0 degrees celsius and 85.0 degrees celsius

**Dc Leakage At Maximum Operating Temp:**

8.0 microamperes

**Nonderated Continuous Voltage Rating And Type Per Section:**

10.0 dc all sections

**Tolerance Range Per Section:**

-10.00/+10.00 percent all sections

**Case Material:**

Plastic

**Capacitive Electrode Material:**

Tantalum

**Dissipation Factor At Reference Temperature In Percent:**

6.0000

**Dc Leakage At Reference Temp:**

0.020 microamperes

**Terminal Surface Treatment:**

Solder

**Terminal Type And Quantity:**

4 uninsulated wire lead

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A010b0