

View Online at <https://aerobasegroup.com/nsn/5910-01-085-5762>

Body Style:

Dual inline

Reliability Indicator:

Not established

Terminal Length:

0.120 inches

Body Length:

0.860 inches

Body Width:

0.310 inches

Body Height:

0.200 inches

Schematic Diagram Designator:

Two common terminals for each electrode

End Application:

Wasp class lhd; spruance class dd (963); tarawa class lha; tactical data system, an/uva- (v); kidd class ddg; tank, combat, ft, 120mm gun (m1a1)

Capacitance Value Per Section:

0.022 microfarads single section

Nonderated Operating Temp:

Between -55.0 degrees celsius and 125.0 degrees celsius

Temperature Coefficient Of Capacitance Per Section In Ppm Per Deg Celsius:

0.0 single section

Nonderated Continuous Voltage Rating And Type Per Section:

100.0 dc single section

Tolerance Of Temperature Coefficient Per Section In Ppm Per Deg Celsius:

-15.0/+15.0 single section

Criticality Code Justification:

Feat

Tolerance Range Per Section:

-10.00/+10.00 percent single section

Case Material:

Ceramic

Insulation Resistance At Reference Temp:

100000.0 megohm-microfarads

Dissipation Factor At Reference Temperature In Percent:

2.5000

Special Features:

Weapon system essential

Terminal Type And Quantity:

16 pin

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A010b0