Electrolytic Fixed Capacitor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5910-01-085-8361

### **Body Style:**

W/o mtg facilities, terminal (s) on one end

### **Reliability Indicator:**

Not established

## Terminal Length:

1.181 inches

### **Body Diameter:**

0.248 inches

#### **Body Length:**

0.433 inches

### Center To Center Distance Between Terminals Parallel To Diameter:

0.098 inches

#### **Terminal Diameter:**

0.024 inches

#### Schematic Diagram Designator:

No common or grounded electrode (s)

### **Electrical Polarization:**

Polarized

### **Capacitance Value Per Section:**

10.000 microfarads single section

### Nonderated Operating Temp:

Between -40.0 degrees celsius and 85.0 degrees celsius

### Nonderated Continuous Voltage Rating And Type Per Section:

25.0 dc single section

### **Tolerance Range Per Section:**

-10.00/+50.00 percent single section

#### **Case Material:**

Metal

#### **Capacitive Electrode Material:**

Aluminum

### **Dissipation Factor At Reference Tempurature In Percent:**

15.0000

# Dc Leakage At Reference Temp:

8.000 microamperes

# **Terminal Surface Treatment:**

Solder

# Case Insulation Material:

Plastic

# Terminal Type And Quantity:

2 uninsulated wire lead

# Shelf Life:

N/a

Electrolytic Fixed Capacitor - Page 2 of 2



Unit Of Measure:

---

Demilitarization:

No

Fiig:

A010b0