

View Online at <https://aerobasegroup.com/nsn/5910-01-086-9310>

Body Style:

W/o mtg facilities, axial terminals

Mil-std-1276 Wire Lead Type Designator:

N-3 and c

Reliability Indicator:

Not established

Terminal Length:

Between 2.000 inches and 2.500 inches

Body Diameter:

0.312 inches

Body Length:

0.796 inches

Terminal Diameter:

Between 0.023 inches and 0.027 inches

Schematic Diagram Designator:

Feedthrough

Anode Type:

Solid

Impedance At Minimum Operating Temperature In Ohms:

300.0

Electrical Polarization:

Polarized

Features Provided:

Hermetically sealed case

Capacitance Value Per Section:

5.600 microfarads single section

Nonderated Operating Temp:

Between -55.0 degrees celsius and 85.0 degrees celsius

Dc Leakage At Maximum Operating Temp:

7.0 microamperes

Nonderated Continuous Voltage Rating And Type Per Section:

150.0 dc single section

Tolerance Range Per Section:

-10.00/+10.00 percent single section

Case Material:

Metal

Capacitive Electrode Material:

Tantalum

Dc Leakage At Reference Temp:

2.000 microamperes

Case Insulation Material:

Plastic

Terminal Type And Quantity:

2 uninsulated wire lead

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A010b0