NSN 5910-01-086-9314

Paper-plastic Dielectric Metallized Fixed Capacitor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5910-01-086-9314

Body Style:				
W/o mtg facilities, axial terminals				
Reliability Indicator:				
Established				
Reliability Failure Rate Level In Percent:				
1.0000				
Terminal Length:				
1.625 inches				
Body Diameter:				
0.170 inches				
Body Length:				
0.500 inches				
Terminal Diameter:				
0.025 inches				
Schematic Diagram Designator:				
No common or grounded electrode (s)				
Features Provided:				
Hermetically sealed case				
Capacitance Value Per Section:				
20.010 microfarads single section				
Nonderated Operating Temp:				
Between -55.0 degrees celsius and 100.0 degrees celsius				
Nonderated Continuous Voltage Rating And Type Per Section:				
30.0 dc single section				
Tolerance Range Per Section:				
-1.00/+1.00 percent single section				
Case Material:				
Metal				
Insulation Resistance At Reference Temp:				
300000.0 megohm-microfarads				
Dissipation Factor At Reference Tempurature In Percent:				
0.1500				
Case Insulation Material:				
Plastic				
Test Data Document:				
81349-mil-c-39002/9 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification				
ormat; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain				
environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).				
Terminal Type And Quantity:				
2 uninsulated wire lead				
Shelf Life:				
N/a				

--

Unit Of Measure:

NSN 5910-01-086-9314

Paper-plastic Dielectric Metallized Fixed Capacitor - Page 2 of 2



	tariz	

No

Fiig:

A010b0