NSN 5910-01-087-5233

Glass Dielectric Variable Capacitor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5910-01-087-5233 **Body Style:** Piston **Overall Length:** 1.213 inches **Terminal Length:** 1.250 inches First Flat Length: 0.218 inches single shaft Flat Height: 0.075 inches single shaft **Shaft Diameter:** 0.160 inches single shaft **Shaft Length:** 0.343 inches single shaft **Body Length:** 0.870 inches **Overall Diameter:** 0.250 inches Tempurature Coefficient Of Capacitance In Ppm Per Deg Celsius: 0.0 single section **Tolerance Of Tempurature Coefficient In Ppm Per Deg Celsius:** -50.0/+50.0 single section **Center To Center Distance Between Terminals Parallel To Length:** 0.703 inches **Terminal Diameter:** 0.032 inches **Quality Factor At 25 Deg Celsius:** 650.0 **Inclosure Type:** Encapsulated **Adjustment Device Torque:** Between 1.000 inch-ounces and 5.000 inch-ounces Insulation Dc Resistance At 25 Deg Celsius:

10.0 gigohms **Mounting Facility Type And Quantity:** 2 terminal **Nonderated Operating Temp:** Between -55.0 degrees celsius and 125.0 degrees celsius **Shaft Type:** Round, flatted single shaft **Capacitance Range In Picofarads:** +0.8/+12.0 single section

NSN 5910-01-087-5233

Glass Dielectric Variable Capacitor - Page 2 of 2



Nonderated Voltage Rating And Type:
750.0 dc continuous single section
Adjustment Device Drive Type And Quantity:
1 shaft
Terminal Type And Quantity:
2 wire lead
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No

Fiig: A096a0