NSN 5910-01-087-5743

Electrolytic Fixed Capacitor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5910-01-087-5743

Body Style:
W/o mtg facilities, terminal (s) on one end
Reliability Indicator:
Not established
Terminal Length:
0.250 inches
Body Diameter:
1.375 inches
Body Length:
4.218 inches
Center To Center Distance Between Terminals Parallel To Diameter:
0.562 inches
Terminal Diameter:
0.190 inches
Schematic Diagram Designator:
No common or grounded electrode (s)
Anode Type:
Plain foil
Electrical Polarization:
Polarized
Capacitance Value Per Section:
1000.000 microfarads single section
Nonderated Operating Temp:
Between -40.0 degrees celsius and 85.0 degrees celsius
Dc Leakage At Maximum Operating Temp:
15.0 milliamperes
Nonderated Continuous Voltage Rating And Type Per Section:
50.0 dc single section
Tolerance Range Per Section:
-0.00/+100.00 percent single section
Case Material:
Metal
Capacitive Electrode Material:
Aluminum
Equivalent Series Resistance At Reference Tempurature In Ohms:
0.047
Dc Leakage At Reference Temp:
2.500 milliamperes
Case Insulation Material:
Plastic
Test Data Document:
04240 mile 20040 anneiliantian (includes anning sing time bulleting, breakungs, etc., that reflect anneiliantian time data in a reflection

81349-mil-c-39018 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

NSN 5910-01-087-5743 Electrolytic Fixed Capacitor - Page 2 of 2



Fiig: A010b0