NSN 5910-01-087-8472

Ceramic Dielectric Variable Capacitor - Page 1 of 1



| View Online at https://aerobasegroup.com/nsn/5910-01-087-8472 |
|---|
| Body Style: |
| Rotary |
| Body Diameter: |
| 0.300 inches |
| Body Height: |
| 0.257 inches |
| Tempurature Coefficient Of Capacitance In Ppm Per Deg Celsius: |
| 750.0 single section |
| Quality Factor At 25 Deg Celsius: |
| 500.0 |
| Inclosure Type: |
| Encased |
| Adjustment Device Torque: |
| Between 11.000 inch-ounces and 48.300 inch-ounces |
| Insulation Dc Resistance At 25 Deg Celsius: |
| 10.0 gigohms |
| Mounting Facility Type And Quantity: |
| 3 terminal |
| Nonderated Operating Temp: |
| Between -55.0 degrees celsius and 85.0 degrees celsius |
| Capacitance Range In Picofarads: |
| +4.5/+20.0 single section |
| Nonderated Voltage Rating And Type: |
| 160.0 dc continuous single section |
| Capacitance Change In Percent At Operating Tempurature From 25 Deg Celsius: |
| +1.75/+8.00 single section and -5.75/-1.75 single section |
| Adjustment Device Drive Type And Quantity: |
| 1 slotted screw |
| Terminal Type And Quantity: |
| 3 printed circuit |
| Shelf Life: |
| N/a |
| Unit Of Measure: |
| |
| Demilitarization: |
| No |
| Fiig: |
| A096a0 |