

View Online at <https://aerobasegroup.com/nsn/5910-01-087-8473>

**Body Style:**

Rectangular prism

**Overall Length:**

0.875 inches

**Overall Height:**

0.725 inches

**Overall Width:**

0.650 inches

**Temperature Coefficient Of Capacitance In Ppm Per Deg Celsius:**

75.0 single section

**Tolerance Of Temperature Coefficient In Ppm Per Deg Celsius:**

-75.0/+125.0 single section

**End Application:**

3virginia class cg (41), spruance class dd(963), ticonderoga class cg(47), forrestal class cv, tarawa class lha, kidd class ddg, nimitz class cvn, wasp class lhd, general purpose electronic test equipment, mine countermeasures support(mcs) class(lph-12)

**Inclosure Type:**

Uninclosed

**Mounting Facility Type And Quantity:**

2 terminal

**Nonderated Operating Temp:**

Between -55.0 degrees celsius and 125.0 degrees celsius

**Capacitance Range In Picofarads:**

+2.5/+6.0 single section

**Nonderated Voltage Rating And Type:**

250.0 dc continuous single section

**Adjustment Device Drive Type And Quantity:**

1 slotted screw

**Terminal Type And Quantity:**

2 wire lead

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A096a0