

View Online at <https://aerobasegroup.com/nsn/5910-01-087-8473>

Body Style:

Rectangular prism

Overall Length:

0.875 inches

Overall Height:

0.725 inches

Overall Width:

0.650 inches

Temperature Coefficient Of Capacitance In Ppm Per Deg Celsius:

75.0 single section

Tolerance Of Temperature Coefficient In Ppm Per Deg Celsius:

-75.0/+125.0 single section

End Application:

3virginia class cg (41), spruance class dd(963), ticonderoga class cg(47), forrestal class cv, tarawa class lha, kidd class ddg, nimitz class cvn, wasp class lhd, general purpose electronic test equipment, mine countermeasures support(mcs) class(lph-12)

Inclosure Type:

Uninclosed

Mounting Facility Type And Quantity:

2 terminal

Nonderated Operating Temp:

Between -55.0 degrees celsius and 125.0 degrees celsius

Capacitance Range In Picofarads:

+2.5/+6.0 single section

Nonderated Voltage Rating And Type:

250.0 dc continuous single section

Adjustment Device Drive Type And Quantity:

1 slotted screw

Terminal Type And Quantity:

2 wire lead

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A096a0