Plastic Dielectric Fixed Capacitor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5910-01-088-6087

## **Body Style:**

W/mtg tabs/flanges, terminal (s) on one surface

### **Reliability Indicator:**

Not established

# Mounting Slot Width:

0.500 inches

### **Body Length:**

15.500 inches

#### **Body Width:**

5.000 inches

#### **Body Height:**

#### 14.125 inches

### Center To Center Distance Between Terminals Parallel To Length:

9.000 inches

#### **Terminal Diameter:**

### 0.500 inches

### **Terminal Height From Body:**

6.625 inches

# Distance Between Centerlines Of Mounting Facilities Parallel To Body Length:

17.500 inches

# Schematic Diagram Designator:

No common or grounded electrode (s)

# Distance Between Centerlines Of Mounting Facilities Parallel To Body Width:

3.000 inches

## Mounting Facility Type And Quantity:

4 mounting slots

### **Features Provided:**

Hermetically sealed case

#### Capacitance Value Per Section:

0.500 microfarads single section

#### Nonderated Operating Temp:

Between 15.6 degrees celsius and 50.0 degrees celsius

## Nonderated Continuous Voltage Rating And Type Per Section:

45000.0 dc single section

#### **Tolerance Range Per Section:**

-0.00/+10.00 percent single section

### Case Material:

Metal

# **Terminal Type And Quantity:**

2 standoff, threaded stud

#### Shelf Life:

N/a

Plastic Dielectric Fixed Capacitor - Page 2 of 2



Unit Of Measure:

---

Demilitarization:

No

Fiig:

A010b0